

Features

- **Extended temperature range:**
- 40° to +140°F
- **Standard analog telephone line powered**
- **Anti-corrosive enclosure**
- **Braille metallic keypad**
- **Fully line powered**
(no external power required)
- **Hearing aid compatible**
- **Non-movable hookswitch**
- **Volume control handset**
- **Noise-canceling microphone**
- **Extreme operating temperature range**



256-001 Outdoor Phone



246-001 Indoor Phone



276-001 Flush Panel Phone



226-001 Tough Phone

GAI-Tronics' wide variety of indoor and outdoor Industrial Telephones are designed for those applications where standard telephones are not environmentally suitable. Such applications include public areas, plant entrances, college campuses, airports, commercial locations, parking garages and amusement parks.

GAI-Tronics has been manufacturing rugged industrial communications equipment for over 50 years and consistently strive to meeting and exceed customer requirements. As an ISO9001:2000 certified company, we maintain the highest quality standards and are proud that our equipment is manufactured in the U.S.A.

Since our industrial telephones are often installed in the harshest environments, durability and performance are extremely important.

GAI-Tronics industrial telephones include standard items such as a proximity detecting hookswitch with no moving parts and a sealed keypad to keep out dust, dirt and moisture. The sealed electronic ringer also prevents contaminants from entering the housing. Other standard features are noise-canceling microphones and volume control handset. These telephones are fully line powered, and do not require an internal battery.

The 246 indoor and 256 outdoor series Industrial Telephones are constructed of a high-impact, anti-corrosive enclosure with an industrial strength six-foot Hytrel[®] handset cord. The Hytrel[®] cord is unique that it can withstand 250 pounds of pull-strength and remains flexible in the most extreme temperatures, unlike PVC cords that are limited to 40 pounds of pull-strength and begin to deteriorate at -14°F temperature range.

GAI-Tronics 226 series Tough Phone was developed for public and industrial areas requiring a virtually indestructible telephone. Each Tough Phone is housed in a 1/4-inch thick, sand-cast aluminum enclosure, coated with an exterior polyurethane finish. Standard equipment includes a spring return door, 15-inch lanyard armored cord resistant up to 800 pounds of pull-strength, proximity metallic non-moveable hook-switch and tamper resistant hardware.

The 276 series telephone is designed to flush mount or surface mount (using 236 series enclosure). This unit has a brushed stainless steel faceplate with a metallic non-moveable hook-switch. Standard equipment also includes a 29-inch lanyard armored cord, resistant up to 800 pounds of pull-strength and tamper resistant hardware.

Note: Part number 233 Tamper resistant screwdriver is required for installation of the models 226 and 276 telephones.

Standard Keypad Industrial Telephones

TECHNICAL SPECIFICATIONS

Electrical

Current	Minimum 20mA dc; Maximum 60mA dc
Voltage	24 V dc to 60 V dc (not polarity sensitive)
Signaling	DTMF

Environmental

Operating temperature range	-40° to +60° C -40° to +140° F
Relative humidity	to 95%, no condensation

Model 246-001 and 256-001

Enclosure	High impact, glass reinforced polyester	
Dimensions	246 Series	8 W x 9.5 H x 6.9 D inches
	256 Series	9.4 W x 13.2 H x 7.4 D inches
Weight	246 Series	6.0 lbs.
	256 Series	8.2 lbs.

Model 226-001

Enclosure	1/4 inch thick sand-cast aluminum with protective exterior polyurethane gray finish
Dimensions	13.5 H x 9.7 W x 6.1 D inches
Weight	18 lbs.

Model 276-001

Panel	14-gauge brushed stainless steel
Dimensions	12 H x 10 W inches
Weight	6.5 lbs.

Ringer Level (avg. @ 2 ft.)

Model	Door Open	Door Closed
226 Series	92 dBA SPL	74 dBA SPL
246 Series	92 dBA SPL	N/A
256 Series	91 dBA SPL	84 dBA SPL
276 Series	86 dBA SPL	N/A

Approvals

Safety of Information Technology Equipment	UL/CSA 60950
Enclosures for Electrical Equipment	UL 50, Type 3R

47 CFR Party 68

Certification Number	US: ADGTE10A-46048HAC
Ringer Equivalence Number	1.3B
Network connections (USOC)	RJ11

IC Information (Canada)

IC Certification Number	82211754
Ringer Equivalence Number	1.3B
Connection Method	CA11A

Pole-Mount Kits

230 Pole-mounting kit for 256 Series
231 Pole-mounting kit for 246 Series
232 Pole-mounting kit for 226 Series
233 Tamper Resistant Screw Driver for 276 Series and 226 Series phones
236YL, 236RD and 236BK: Wall-mount enclosures for surface mounting 276 series

Option Accessories

Order Code	Description	Available on Models			
		226 Series	246 Series	256 Series	276 Series
AC	15" Armored Cord	STD	*	*	
A2	29" Armored Cord		*	*	STD
H1	15' Hytrel® Cord		*		*
H2	25' Hytrel® Cord		*		*
SK	Spring Door Return	STD		*	
LD	Keylock Door	*		*	
TR	PCBA Conformal Coating	*	*	*	*
Consult Factory For Special Paint		*		*	

Pub. 040804 Rev. 11-2008



GAI-Tronics® USA (Corporate) Toll Free: 1 (800) 492-1212 Tel: (610) 777-1374 Fax: (610) 796-5954 www.gai-tronics.com
 GAI-Tronics® UK Tel: +44 (0)1283 500500 Fax: +44 (0)1283 500400 www.gai-tronics.co.uk
 GAI-Tronics® S.r.l - Italy Tel: +39 02 4588801 Fax: +39 02 93663110 www.gai-tronics.it
 GAI-Tronics® Malaysia Tel: +60-3-8945-4035 / 8945-7348 Fax: +60-3-8945-4675 www.gai-tronics.com
 GAI-Tronics® Austdac - Australia Tel: 011-61-28-851-5000 Fax: 011-61-29-899-2490 www.austdac.com.au

Quality Management System Certified by DNV - ISO9001:2008

The policy of GAI-Tronics is one of continuous improvement; therefore the company reserves the right to change specifications without notice.